

TANGENTIAL GRINDING MACHINE FAVRETTO TD 200



Example picture

TECHNICAL DATA

WORKING CAPACITY:

| | |
|----------------------|----------|
| Max grinding length: | mm 2.000 |
| Max grinding width: | mm 700 |
| Max grinding height: | mm 500 |

TABLE:

| | |
|--|----------------|
| Length of the fixing grooves: | mm 2.400 |
| Useful dimensions of the support surface: | mm 2.000 x 600 |
| Dimensions and distance between the three T-slots: | mm 14 x 200 |
| Max longitudinal stroke: | mm 2.130 |
| Continuously adjustable speed: | m/min 2 ÷ 35 |

GRINDING WHEEL:

| | |
|-----------------------------------|--------------|
| Normal dimensions (diam. x hole): | mm 457 x 203 |
| Normal width: | mm 100 |
| Speed with 50 Hz motor: | rpm 960 |
| Max transverse stroke: | mm 600 |

| | |
|--|------------------|
| Intermittent transverse feeds: | mm 1 ÷ 10 |
| Adjustable transverse movements in continuation: | m/min 0.1 ÷ 6 |
| Automatic vertical feeds: | mm 0.005 ÷ 0.05 |
| <u>MISCELLANEOUS:</u> | |
| Overall dimensions: | mm 5.760 x 1.770 |
| Weight: | kg 9,300 |